




























Model No.	Range	Product Description	Photos	Resolution	Lens	DORI	IR Distance
TC-C321N Spec:13/E/Y/2.8mm/V2.0	AK Series	IP Camera: 1/3" CMOS Sensor with IR CUT (0.02Lux). S+265/H.265/H.264B(M)(H), DWDR, BLC and HLC. 1CH MIC. Plastic Housing		Entry Level 1080P (2MP) Motion Detection Only	2.8mm	D : 40M O : 16M R : 8M I : 4M	30M
TC-C320N Spec:13/E/Y/2.8mm/V2.0							
TC-C328N Spec:15/E/Y/QX/2.8mm/V4.2	Spark	IP Omni Camera with Dual Image Sensor: 1/3" CMOS Sensor with IR CUT (0.02Lux). S+265/H.265/H.264B(M)(H), DWDR, BLC and HLC. 1CH MIC. Plastic Housing				D : 42M O : 16M R : 8M I : 4M	50M
TC-C320N Spec:15W/E/Y/2.8mm/V4.2	Color Maker	IP Camera: 1/2.8" CMOS Sensor with IR CUT (0.02Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), DWDR, BLC and HLC. 1CH MIC, SD Card Slot. Metal & Plastic Housing		Mid Range 1080P (2MP) Basic Analytics	2.8mm	D : 38M O : 15M R : 7M I : 4M	50M IR & 15M White Light Assisted
TC-C32XN Spec:13W/E/Y/2.8mm/V4.2							Mid Range 4MP Basic Analytics
TC-C340N Spec:15W/E/Y/2.8mm/V4.2				Mid Range 4MP Basic Analytics		50M IR & 15M White Light Assisted	
TC-C34XN Spec:13W/E/Y/2.8mm/V4.2						30M IR & 15M White Light Assisted	
TC-C32WS Spec:15W/E/Y/S/2.8mm/V5.0	Lite SMD	IP Camera: 1/2.8" CMOS Sensor with IR CUT (0.002Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, SD Card Slot. Metal & Plastic Housing		Advanced 1080P (2MP) Classification (Human & Vehicle)	2.8mm	D : 38M O : 15M R : 8M I : 4M	50M
TC-C32XS Spec:13W/E/Y/S/2.8mm/V5.0							30M
TC-C32US Spec:18/A/E/Y/M/S/H/2.7-13.5mm/V4.0	Pro SMD	IP Camera: 1/2.8" CMOS Sensor with IR CUT (0.002Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Audio I/O, Alarm I/O, SD Card Slot. Metal Housing		Advanced 1080P (2MP) Classification (Human & Vehicle) Face Capture	2.7-13.5mm	D : 39~165M O : 15~65M R : 7~33M I : 3~16M	80M
TC-C32SS Spec:13/A/E/Y/M/S/H/2.7-13.5mm/V4.0							30M
TC-C35WS Spec:15W/E/Y/S/2.8mm/V5.0	Lite SMD	IP Camera: 1/2.8" CMOS Sensor with IR CUT (0.002Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, SD Card Slot. Metal & Plastic Housing		Advanced SMP Classification (Human & Vehicle)	2.8mm	D : 56M O : 22M R : 11M I : 6M	50M
TC-C35XS Spec:13W/E/Y/S/2.8mm/V5.0							30M
TC-C34UV Spec:W/E/Y/M/S/4mm	Lite Polar Day	IP Camera: 1/1.8" CMOS Sensor with IR CUT (0.0003Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Audio I/O, Alarm I/O, SD Card Slot. Metal Housing		Advanced 4MP Classification (Human & Vehicle)	4mm	D : 80M O : 32M R : 16M I : 8M	15M Warm White Light
TC-C34LQ Spec:13W/A/E/Y/M/H/2.8-12mm/V4.2	Pro ANPR	IP Camera: 1/1.8" CMOS Sensor with IR CUT (0.0004Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Audio I/O, Alarm I/O, SD Card Slot. Metal Housing		Advanced 4MP Classification (Human & Vehicle)	2.8-12mm	D : 37~160M O : 14~64M R : 7~32M I : 3~16M	80M
TC-C35WQ Spec:15W/E/Y/2.8mm/V4.2	Pro Early Warning	IP Camera: 1/2.7" CMOS Sensor with IR CUT (0.002Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Speaker, Audio I/O, Alarm I/O, SD Card Slot. Metal Housing		Advanced SMP Classification (Human & Vehicle) Face Capture	2.8mm	D : 56M O : 22M R : 11M I : 6M	50M
TC-C35VN Spec:13/E/Y/1.4mm/V4.2	Lite Fisheye	IP Camera: 1/2.7" CMOS Sensor with IR CUT (0.02Lux). ONVIF Profile S/T/G, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Audio I/O, Alarm I/O, SD Card Slot. Plastic Housing		Entry SMP Heat Map Tripwire	1.4mm	D : 24M O : 9M R : 5M I : 3M	30M
TC-C35LQ Spec:15W/E/Y/T/6mm/V4.2	Pro Thermal	IP Camera: Dual Image Sensor. 1/2.7" CMOS Sensor with IR CUT (0.002Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Speaker, Audio I/O, Alarm I/O, SD Card Slot. Metal Housing		Advanced Visual SMP Thermal QCIF Tripwire	6mm	D : 120M O : 48M R : 24M I : 12M	50M
TC-C382V Spec:W/E/Y/S/H/2.8mm	Pro Panoramic	IP Camera: Dual Image Sensor. 1/2.7" CMOS Sensor with IR CUT (0.0001Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Speaker, Audio I/O, Alarm I/O, SD Card Slot. Metal Housing		Advanced 8MP Classification (Human & Vehicle)	2.8mm	D : 56M O : 22M R : 11M I : 6M	10M Warm White Light
TC-H324S Spec:23X/I/E/V3.0	Pro SMD	IP Camera: 4" PTZ Dome Camera: 1/2.8" CMOS Starlight sensor with IR CUT (0.001 Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, DNR and AGC. TVS 6KV lightning protection. 24VDC, Waterproof IP66. Aluminium & Plastic Housing		Advanced 2MP Classification (Human & Vehicle)	5-115mm 23x Optical	D : 1351M O : 536M R : 270M I : 135M	
TC-H324S Spec:25X/I/E/V3.0	Pro AI+	IP Camera: 4" PTZ Dome Camera with Auto Tracking: 1/2.8" CMOS Starlight sensor with IR CUT (0.001 Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, DNR and AGC. TVS 6KV lightning protection. 24VDC/PoE+, Waterproof IP66. Aluminium & Plastic Housing		Advanced 2MP Classification (Human & Vehicle) Face Capture	4.8-120mm	D : 1517M O : 602M R : 303M I : 151M	150M
TC-H344S Spec:25X/I/E/V3.0		IP Camera: 4" PTZ Dome Camera with Auto Tracking: 1/2.7" CMOS Starlight sensor with IR CUT (0.001 Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, DNR and AGC. TVS 6KV lightning protection. 24VDC/PoE+, Waterproof IP66. Aluminium & Plastic Housing		Advanced 4MP Classification (Human & Vehicle) Face Capture	25x Optical	D : 1980M O : 785M R : 396M I : 198M	
TC-H348M Spec:63X/I/E+/A	Ultra Laser	IP Camera: 8" PTZ Dome Camera with Auto Tracking and Early Warning: 1/1.8" CMOS Starlight sensor with IR CUT (0.001 Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, DNR and AGC. TVS 6KV lightning protection. 36VDC/PoE+, Waterproof IP66. Aluminium & Plastic Housing		Advanced 4MP Classification (Human & Vehicle) Face Capture	4.8-120mm 63x Optical	D : 3800M O : 1508M R : 760M I : 380M	500M Laser
TC-H366V Spec:4MP/25X/I/E+/A/2.8mm	Ultra Panoramic	IP Camera Multi Sensor: 6" PTZ Dome Camera with 3D Position Support and Early Warning: Pans: 1.18" CMOS, Detail: 1/2.7" CMOS Starlight sensor with IR CUT (0.0001 Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), DWDR, DNR and AGC. TVS 6KV lightning protection. 24VDC/PoE+, Waterproof IP66. Aluminium & Plastic Housing		Advanced 6MP Classification (Human & Vehicle) Face Capture	5.7-359mm 25x Optical	D : 45~110~2200M O : 18~43~880M R : 9~22~444M I : 5~11~222M	150M
TC-H358M Spec:44X/I/T/A	Ultra Thermal	IP Camera: 8" Dual Image Sensor PTZ Dome Camera with Auto Tracking: 1/2.7" CMOS Starlight sensor with IR CUT (0.001 Lux). ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, DNR and AGC. TVS 6KV lightning protection. 24VDC, Waterproof IP66. Aluminium & Plastic Housing		Advanced Visual SMP Thermal CF Classification	6-264mm 44x Optical 50mm Thermal	D : 4510(V)~1471(H)M O : 1127(V)~368(H)M R : 564(V)~184(H)M	300M



Model No.	Range	Product Description	Photos	Resolution	Lens	DORI	IR Distance
TC-C35US Spec:18/A/E/Y/M/S/H/2.7-13.5mm/V4.0	Pro SMD	IP Camera: 1/2.7" CMOS Sensor with IR CUT (0.002Lux), ONVIF Profile S/T/G/M, S+265/H.265/H.264B(M)(H), TWDR, BLC and HLC. 1CH MIC, Audio I/O, Alarm I/O, SD Card Slot. Metal Housing		Advanced SMP Classification (Human & Vehicle) Face Capture	2.7-13.5mm	D : 56°-240M O : 22°-95M R : 11°-48M I : 6°-24M	80M
TC-C35SS Spec:13/A/E/Y/M/S/H/2.7-13.5mm/V4.0			30M				

CENTURION BRANCH
TEL: 012 653 8881
WHATSAPP: 072 298 2420

info@skynatics.com
www.skynatics.com

EDENVALE BRANCH
TEL: 011 454 5463
WHATSAPP: 063 975 1089



Model No.	Range	Product Description	Photos	Resolution	Display Output	SATA	PoE Ports
TC-R3108 Spec: I/B/P8/C/Eu/L/S	AK Series	8CH Embedded Linux NVR: S+265/H.265/H.264B(M)(H) compression, 2x USB, LAN, IR-Remote & Mouse. Aluminium & Plastic Housing		Up to 6MP	HDMI up to 4K Resolution	1	8 Port
TC-R3210 Spec: I/B/K/V3.1	Lite	10CH Embedded Linux NVR: S+265/H.265/H.264B(M)(H) compression, ANR.N+M, I/O - 4/1, 2x USB, LAN, IR-Remote & Mouse. Aluminium Housing		Up to 8MP	HDMI / VGA (Simultaneous) 4K Resolution	2	-
TC-R3210 Spec: I/B/P8/K/V3.1		8					
TC-R3220 Spec: I/B/K/V3.1		-					
TC-R3220 Spec: I/B/P16/K/V3.1		16					
TC-R3240 Spec: I/B/N/H/V4.0	Pro	40CH Embedded Linux NVR: S+265/H.265/H.264B(M)(H) compression, ANR.N+M, I/O - 16/4, 2x USB, 2x LAN, IR-Remote & Mouse. Aluminium Housing		Up to 12MP	HDMI / VGA (Non Simultaneous) 4K Resolution	4	-
TC-R3440 Spec: I/B/N/V4.0		16					
TC-R3440 Spec: I/B/P16/H/V4.0		-					
TC-R3880 Spec: I/B/N/V4.0		8					
TC-K14	4 Camera Kit with 8CH Recorder	Including: 8CH Embedded Tiandy NVR with onboard PoE (TC-R3108 I/B/P8/C/Eu/L/S) 1TB Western Digital Surveillance HDD 4x 2MP AK Series Dome or Bullet Network Cameras (TC-C320N & TC-C321N) 4x 30M Pre-Made Network Cable					8 Port
TC-Omni2	2 Camera Omni Kit with 8CH Recorder	Including: 8CH Embedded Tiandy NVR with onboard PoE (TC-R3108 I/B/P8/C/Eu/L/S) 1TB Western Digital Surveillance HDD 2x 2MP Spark Omni Cameras (TC-C32RN) 2x 30M Pre-Made Network Cable					8 Port